



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM1		Z1	1F	2F	3F	4F	5F	6F	Z4			1	6A	5A	4A	3A	COL2	2A	1A	COM1
COM2		Z2	1G	2G	3G	4G	5G	6G	Z5	COM2		2	6B	5B	4B	3B	COL1	2B	1B	
COM3	COM3	Z3	1E	2E	3E	4E	5E	6E	Z6			3	6C	5C	4C	3C		2C	1C	
COM4			1D	2D	3D	4D	5D	6D	Z7	COM4		4	6P	5P	4P	3P		2P	1P	

NOTE:A&B

1. DISPLAY TYPE: TN-POSITIVE-REFLECTIVE
2. VIEWING DIR.: 6:00
3. DRIVE METHOD: 1/4DUTY, 1/3BIAS
4. OP. TEMP.: 0°C~50°C
5. ST. TEMP.: -10°C~60°C
6. CONNECTOR TYPE : PIN
7. POLARIZER TYPE : T/R
8. VOLTAGE.: A:3.5V B:3.0V

NOTE:C

1. DISPLAY TYPE: TN-POSITIVE-REFLECTIVE
2. VIEWING DIR.: 6:00
3. DRIVE METHOD: 1/4DUTY, 1/3BIAS
4. OP. TEMP.: -20°C~70°C
5. ST. TEMP.: -30°C~80°C
6. CONNECTOR TYPE : PIN
7. POLARIZER TYPE : T/R
8. VOLTAGE.: 3.5V

 石家庄冠晶电子科技有限公司

型号	图号
制图	日期
审核	页数
批准	
缩版尺寸	X:0.1 Y:0.1