



PIN 1	2	3	4	5	6	7	8	9	10	11	12	13	14
COM	COM	E1	D1	C1	DP1	E2	D2	C2	DP2	E3	D3	C3	DP3
PIN 15	16	17	18	19	20	21	22	23	24	25	26	27	28
COM	C2	DP2	E3	D3	C3	DP3	E4	D4	C4	DP4	E5	D5	C5
PIN 29	30	31	32	33	34	35	36	37	38	39	40	41	42
COM	D4	C4	DP4	E5	D5	C5	DP5	E6	D6	C6	DP6	E7	D7
PIN 43	44	45	46	47	48	49	50	51	52	53	54	55	56
COM	E6	D6	C6	B6	A6	F6	G6	A7	B7	C7	D7	E7	F7
PIN 57	58	59	60	61	62	63	64	65	66	67	68	69	70
COM	B5	A5	F5	G5	COL2	B4	A4	F4	G4	COL1	B3	A3	F3
PIN 71	72	73	74	75	76	77	78	79	80	81	82	83	84
COM	F4	G4	B3	A3	F3	G3	COL1	B2	A2	F2	G2	B1	A1
PIN 85	86	87	88	89	90	91	92	93	94	95	96	97	98
COM	B2	A2	F2	G2	B1	A1	F1	G1	COL1	B1	A1	F1	G1
PIN 99	100												
COM	G1												

NOTE:

1. DISPLAY TYPE: TN, POSITIVE, TRANSMISSIVE
2. VIEWING DIR.: 6:00
3. DRIVE METHOD: STATIC, Vop5V
4. DP, TEMP.: -30°C~80°C
5. ST, TEMP.: -40°C~90°C
6. UV, FILTER POLARIZER

石家庄冠晶电子科技有限公司

型号	图号
制图	日期
审核	页数
批准	

缩版尺寸 X:0.1 Y:0.1